



- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 110lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- 24V DC Electronic Led driver positioned inside luminaire.
- Steel suspension cord with up to 5mt lenght option.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzör.
- 220-240V / 50-60Hz enerji giriřli.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 110lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bađlı özel renk seçenekleri mevcuttur.
- 24V DC Led trafosu armatürün içindedir.
- 5mt uzunluk seçeneđine kadar tercih edilebilir çelik sarkıt tel.

Sivo / I02.LL.13150.60

Order Code / Ürün Kodu	I02.LL.13150.60	
LED	SMD LED	
Led Power / Led Gücü	23W	
System Power / Sistem Gücü	25W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	2470
	3000K	2545
	3500K	2600
	4000K	2650
	5000K	2730
Product Diameter / Ürün Çapı (A)	Ø600mm	
Product Diameter / Ürün Çapı (B)	Ø450mm	
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	
1-10V Dimming Option / 1-10V Dim Seçeneđi	✓	
Dali Dimming Option / Dali Dim Seçeneđi	✓	

Suspension Cord

Ray Sarkıtma Teli

