



- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 110lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- 24V DC Electronic Led driver positioned inside luminaire.
- Surface mounting wadge positioned backside of the luminaire.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzörlü.
- 220-240V / 50-60Hz enerji giriřli.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 110lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe baęlı özel renk seçenekleri mevcuttur.
- 24V DC Led trafosu armatürün içindedir.
- Sıvaüstü montaj takozu armatürün arkasına montelidir.

Sivo / I02.LL.13156.75

| Order Code / Ürün Kodu | I02.LL.13156.75 | |
|---|-----------------|------|
| LED | SMD LED | |
| Led Power / Led Gücü | 37W | |
| System Power / Sistem Gücü | 40W | |
| Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80 | 2700K | 4025 |
| | 3000K | 4150 |
| | 3500K | 4233 |
| | 4000K | 4320 |
| | 5000K | 4445 |
| Product Diameter / Ürün Çapı (A) | Ø750mm | |
| Product Diameter / Ürün Çapı (B) | Ø600mm | |
| Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu | ✓ | |
| 1-10V Dimming Option / 1-10V Dim Seçeneęi | ✓ | |
| Dali Dimming Option / Dali Dim Seçeneęi | ✓ | |

Wadge

Takoz

