



- Aluminium profile body.
- Plastic end caps.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V and DALI dimming options available upon request.
- High efficient matt anodized aluminium parabolic reflector.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- Up to 110lm/W efficiency.
- Tilttable light heads.
- Emergency kit system can be integrated.

- Alüminyum profil gövde.
- Plastik kapak.
- 220-240V / 50-60Hz enerji girişi.
- Akıllı soğutma tasarımı.
- 1-10V ve DALI dim seçenekleri bulunmaktadır.
- Yüksek verimli parabolic mat anodize alüminyum reflektörü.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- 110lm/W'a kadar verim.
- Yönlendirilebilir ışık gövdesi.
- Acil aydınlatma kit sistemi uygulanabilir.

Rood / I02.LL.19212.V1

SMD LED	.28	.37	.46
Led Power / Led Gücü	26W	34W	43W
System Power / Sistem Gücü	28W	37W	46W
Lumen Output from Fixture / Armatür Çıkışı Lümeni CRI>80	2700K	2830	3775
	3000K	2918	3890
	3500K	3005	4005
	4000K	3095	4125
	5000K	3190	4250
Lenght / Uzunluk (A)	900mm	1180mm	1460mm
Ceiling Cutout Dimension / Tavan Delik Ölçüsü	X	X	X
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	X	X	X
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓

Wadge

Takoz

