



- Aluminium profile body.
- Plastic end caps.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V and DALI dimming options available upon request.
- High efficient lens optic with narrow, medium, wide and double assymetric light distribution.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- Over 120lm/W efficiency.
- Emergency kit system can be integrated.
- Continious line installation possible with trunking system.
- 'Click-fit' system with BJB holder integration.

- Alüminyum profil gövde.
- Plastik kapak.
- 220-240V / 50-60Hz enerji girişli.
- 1-10V ve DALI dim seçenekleri bulunmaktadır.
- Dar, orta, geniş ve çift asimetrik ışık dağılımı seçeneklerini içeren verimli lens optik.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- 120lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Lineer kesintisiz montaj sistemine uyumlu.
- BJB duy entegrasyonu ile 'click-fit' sistemine sahip.

### Axis / I02.LL.19430.V2

LED	SMD LED	
Led Power / Led Gücü	39W	
System Power / Sistem Gücü	42W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	4695
	3000K	4840
	3500K	4985
	4000K	5140
	5000K	5290
Lenght / Uzunluk (A)	1440mm	
Ceiling Cutout Dimension / Tavan Delik Ölçüsü	X	
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	X	
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	
Dali Dimming Option / Dali Dim Seçeneği	✓	

