



Geo / O07.BL.07525

Code / Kod	BL.07525	
System Power / Sistem Gücü	2x22W	
Lumen Output from Fixture / Armatür Çıkış Lümeni CRI>80	2700K	2x2545
	3000K	2x2595
	3500K	2x2650
	4000K	2x2703
	6000K	2x2785
Dali Dimming Option / Dali Dim Seçeneği	✓	
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	

EN

- Corrosion resistant aluminium body.
- Mains voltage: 220-240V / 50-60Hz.
- Spot, medium and wide beam angle options available.
- Convenient to be used with power led.
- Led colour temperatures are optionally 2700K, 3000K, 3500K, 4000K and 6000K.
- Thermal shock resistant tempered glass.
- Weatherproof and durable silicone rubber gasket.
- Ultraviolet stabilized polyester powder coat finish in white, black, dark gray and light gray finish.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- All external screws are stainless steel.
- High colour consistency: <3 SDCM
- Up to 123lm/W efficiency.
- DALI and 1-10V dimming options available.

TR

- Korozyona dayanıklı alüminyum gövde.
- 220-240V / 50-60Hz enerji girişi.
- Dar, orta ve geniş açı seçenekleri mevcuttur.
- Power Led ile kullanıma uygundur.
- 2700K, 3000K, 3500K, 4000K ve 6000K renk sıcaklığı seçenekleri mevcuttur.
- Termal şoka dayanıklı cam.
- Su geçirmezliği sağlayan silikon conta.
- Ultraviyole ışımaya dayanıklı beyaz, açık gri, antrasit gri ve siyah elektrostatik toz boyalı.
- Çift katmanlı polyester toz boya sayesinde korozyona ve tuza dayanıklı gövde.
- Tüm dış civatalar paslanmaz çelik.
- Yüksek LED renk uyumu: <3 SDCM
- 123lm/W değerine ulaşan verim.
- DALI ve 1-10V dim seçenekleri mevcuttur.